

PREDATOR® 750 PORTABLE AIR SCRUBBER

The Best & Most Mobile HEPA Filtration Device in its Class

- ▶ Variable speed airflow, with maximum rated airflow as high as 750cfm
- ▶ Ultra-compact, light weight cabinetry, integral ergonomic lift handle and perfect weight balance
- ▶ Easy to clean polymer cabinet treated with microbial growth & UV inhibitors
- ▶ “Zero Bypass” cabinet design
- ▶ Easy access for fast pre-filter and HEPA filter replacement
- ▶ Custom colors available



▶ SPECIFICATIONS	▶ PRED750
Net Weight With Filters	35 pounds
Shipping Weight	43 pounds
Dimensions (LxWxH)	25.5”L x 19.5”W x 20.5”H
Power Supply Requirements	110-120 volts AC, 60Hz, 15 amp circuit
Normal Operating Amps	1.9A or less (Daisy-chain up to five units on one 15A circuit)
Motorized Impeller	Motorized impeller with thermal overload protection, auto reset, 60Hz, single phase
Circuit Breaker	12 amp
GFCI Protected Receptacles	Dual receptacles allow for daisy-chaining multiple units on a 15 or 20 amp circuit
Power Cord	25 foot long grounded power cord with cord wrap clip
Cabinet Material	UL94HB flame retardant resin with EPA-Registered microbial inhibitor and UV inhibitor
Filters	<ul style="list-style-type: none"> • Stage 1 pre-filter - 1” coarse particulate pre-filter, 12/cs, p/n F621 • Stage 2 pre-filter - 2” pleated particulate pre-filter, 6/cs, p/n H502 • Optional Stage 2 VAPOR-LOCK® carbon filter, 6/cs, p/n VL1002 • True HEPA filter - Tested and certified to an efficiency of 99.97% or higher against 0.3 micron size particles, 1/ea, p/n H161606-99 • Flex duct, clamps & other accessories also available

NOTE: Airflow ratings estimates are based on factory and independent testing @ 120 VAC with an air straightener and a traverse of readings taken with a computing vane-anemometer. Actual results may vary for various reasons, including motor tolerance. Factors such as reduced voltage to the motor will reduce airflow. Use these ratings as a general guideline only.

Specifications and details are subject to change without prior notice.

US Patent No. 9,868,082
 U.S. Patent No. D742495 / © Abatement Technologies, Inc.
 Canadian Patent No. 156184 / © Abatement Technologies, Inc.



Complete equipment packages available to meet
 the needs of individual contractors

U.S. 1.800.634.9091 | www.abatement.com | iaqinfo@abatement.com